



DIN PC 336x Series, 8-bit GPIO

| Model Type | D-3360-C2G2A | D-3360-C2G2 | D-3360-852G2 | D-3360-222G2 | D-3360-851C1G2 | D-3360-221C1G2 | D-3360-851221G2 | |
|--------------------|---|---------------|--------------|--------------|----------------|----------------|-----------------|------------|
| | D-3362-C2G2A | D-3362-C2G2 | D-3362-852G2 | D-3362-222G2 | D-3362-851C1G2 | D-3362-221C1G2 | D-3362-851221G2 | |
| Processor | DM&P Vortex86DX3 (1GHz) | | | | | | | |
| BIOS | AMI BIOS | | | | | | | |
| Memory | Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series | | | | | | | |
| VGA | Integrated Graphics Chip/ D-Sub 15-pin | | | | | | | |
| Maximum Resolution | 1920 x 1080 pixels | | | | | | | |
| Ethernet | 10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot) | | | | | | | |
| USB 2.0 | External: 2 ports (Front x 2) Internal: 1 port (space reserved dimension 33 x 20mm) | | | | | | | |
| HD Audio | Mic in & Line out | N/A | N/A | N/A | N/A | N/A | N/A | |
| I/O | SD Slot | 1x (Internal) | | | | | | |
| | SATA | 1x | | | | | | |
| | COM1 | RS-232 | RS-232 | RS-485 | RS-422 | RS-485 | RS-422 | RS-485 |
| | COM2 | RS-232 | RS-232 | RS-485 | RS-422 | RS-232 | RS-232 | RS-422 |
| | COM5 | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO |
| | COM6 | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO | 8-bit GPIO |
| Auto Power On | Yes | | | | | | | |
| Power | DC +8V~+24V (Pluggable Terminal Block 3-Pin 5.00mm Pitch) | | | | | | | |
| Dimensions | 152 x 104 x 54mm | | | | | | | |
| Unit Net Weight | 760g | | | | | | | |
| Operation Temp. | 5~50 °C | | | | | | | |
| Certifications | CE, FCC, VCCI | | | | | | | |
| Optional | 1. Mic input/ Line out 2. TTL Level RS-232 | | | | | | | |
| Note | DIN PC with Mic in & Line out does not support 2.5" SATA HDD | | | | | | | |

Features:

- * DM&P Vortex86DX3 (1GHz)
- * Onboard 1GB/ 2GB DDR3
- * SATA DOM support
- * SATA 2.5" HDD, SSD support (Optional)
- * SD, SDHC support (Internal)
- * DIN rail mounting support
- * Fanless design
- * 10/100 Mbps LAN x 1, 1Gbps LAN x 1
- * Wireless LAN Dongle support (Optional)
- * PXE Diskless Boot
- * USB 2.0 port x 3
- * RS-232 Up to 2 ports
- * RS-485 Up to 2 ports
- * RS-422 Up to 2 ports
- * 8-bit GPIO port x 2
- * Auto Power On support
- * Pluggable Terminal Block 3-Pin 5.00mm Pitch