



**EBOX-336x Series, LAN x 2, RS-232, RS-485, CF, SATA**

Model Type	EB-3360-L2C2CF		EB-3360-L2852CF	
	EB-3362-L2C2CF		EB-3362-L2852CF	
Processor	DM&P Vortex86DX3 (1GHz)			
BIOS	AMI BIOS			
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series			
VGA	Integrated Graphics Chip/ D-Sub 15-pin			
Maximum Resolution	1920 x 1080 pixels			
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port			
HD Audio	Line out			
I/O	CF Slot	1x		
	SATA	1x		
	COM1	RS-232	RS-485	
	COM2	RS-232	RS-485	
Auto Power On	Yes			
Power	DC +8V~+24V			
Dimensions	115 x 115 x 35mm			
Unit Net Weight	510g			
Operation Temp.	5~50 °C			
Certifications	CE, FCC, VCCI			
Optional	1. Mic input 2. TTL Level RS-232 3. SATA (not support 2.5" SATA HDD)			

**Features:**

- \* DM&P Vortex86DX3 (1GHz)
- \* Onboard 1GB/ 2GB DDR3
- \* SATA DOM support
- \* CompactFlash support
- \* VESA mounting support
- \* Fanless design
- \* 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- \* Wireless LAN Dongle support (Optional)
- \* PXE Diskless Boot
- \* USB 2.0 port x 4
- \* RS-232 Up to 2 ports
- \* RS-485 Up to 2 ports
- \* Auto Power On support
- \* Ultra low power