



**EBOX-333x Series, LAN x 1, 8-bit GPIO, RS-485, SATA, mPCIe**

Model Type	EB-3330-852G2	EB-3330-851C1G2	EB-3330-852G2P	
	EB-3332-852G2	EB-3332-851C1G2	EB-3332-852G2P	
Processor	DM&P Vortex86DX2 (933MHz)			
BIOS	AMI BIOS			
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series			
VGA	Integrated Graphics Chip/ D-Sub 15-pin			
Maximum Resolution	1920 x 1440 pixels			
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
USB 2.0	External: 3 ports (Front x 2, Rear x 1)			
HD Audio	Line out			
I/O	SD Slot	1x	1x	1x
	SATA	1x	1x	N/A
	mPCIe	N/A	N/A	1x
	COM1	RS-485	RS-485	RS-485
	COM2	RS-485	RS-232	RS-485
	COM3	8-bit GPIO	8-bit GPIO	8-bit GPIO
	COM4	8-bit GPIO	8-bit GPIO	8-bit GPIO
Auto Power On	Yes			
Power	DC +8V~+24V			
Dimensions	115 x 115 x 35mm			
Unit Net Weight	510g			
Operation Temp.	5~50 °C			
Certifications	CE, FCC, VCCI			
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232			
Note	mPCIe (2.5" SATA HDD not support)		SATA (not support 2.5" SATA HDD)	

**Features:**

- \* DM&P Vortex86DX2 (933MHz)
- \* Onboard 1GB/ 2GB DDR2
- \* SATA DOM, 2.5" HDD, SSD support
- \* mPCIe DOM, SSD support
- \* SD, SDHC support
- \* VESA mounting support
- \* Fanless design
- \* 10/100 Mbps LAN x 1

- \* Wireless LAN Dongle support (Optional)
- \* PXE Diskless Boot
- \* USB 2.0 port x 4
- \* 8-bit GPIO port x 2
- \* RS-485 port x 2
- \* Auto Power On support
- \* Ultra low power