

EBOX-333x Series, LAN x 1, RS-232, mPCIe

Model Type	EB-3330-SSP	EB-3330-C1P	EB-3330-C2P	EB-3330-C3P	EB-3330-C4P
	EB-3332-SSP	EB-3332-C1P	EB-3332-C2P	EB-3332-C3P	EB-3332-C4P
Processor	DM&P Vortex86DX2 (933MHz)				
BIOS	AMI BIOS				
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin				
Maximum Resolution	1920 x 1440 pixels				
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio	Line out				
I/O	SD Slot	1x			
	mPCIe	1x			
	COM1	RS-232	RS-232	RS-232	RS-232
	COM2	N/A	RS-232	RS-232	RS-232
	COM3		N/A	RS-232	RS-232
COM4	N/A		N/A	RS-232	
Auto Power On	Yes				
Power	DC +8V~+24V				
Dimensions	115 x 115 x 35mm				
Unit Net Weight	510g				
Operation Temp.	5~50°C				
Certifications	CE, FCC, VCCI				
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot 5. SATA (not support 2.5" SATA HDD)				
Note	RS-232 COM ports in Full 9pin				

Features:

- DM&P Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- mPCIe DOM, SSD support
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-232 Up to 4 ports (Optional)
- Auto Power On support
- Ultra low power

