

EBOX-333x Series, LAN x 1, RS-485, CANbus, mPCIe

Features:

- DM&P Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- mPCIe DOM, SSD support
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-485 Up to 2 ports (Optional)
- RS-232 Up to 2 ports (Optional)
- CANbus port x 1
- Auto Power On support
- Ultra low power



Model Type	EB-3330-B1C1851P	EB-3330-B1C2851P	EB-3330-B1C1852P	EB-3330-B1852P
	EB-3332-B1C1851P	EB-3332-B1C2851P	EB-3332-B1C1852P	EB-3332-B1852P
Processor	DM&P Vortex86DX2 (933MHz)			
BIOS	AMI BIOS			
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series			
VGA	Integrated Graphics Chip/ D-Sub 15-pin			
Maximum Resolution	1920 x 1440 pixels			
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port			
HD Audio	Line out			
I/O	SD Slot	1x		
	mPCIe	1x		
	COM1	RS-485	RS-485	RS-485
	COM2	N/A	RS-232	RS-485
	COM3	RS-232	RS-232	RS-232
COM4	CANbus	CANbus	CANbus	CANbus
Auto Power On	Yes			
Power	DC +8V~+24V			
Dimensions	115 x 115 x 35mm			
Unit Net Weight	510g			
Operation Temp.	5~50°C			
Certifications	CE, FCC, VCCI			
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot 5. SATA (not support 2.5" SATA HDD)			
Note	RS-232 COM ports in Full 9pin			