

## EBOX-333x Series, LAN x 1, RS-485, SATA

Model Type	EB-3330-851	EB-3330-852	EB-3330-851C1	EB-3330-851C2	EB-3330-851C3	
	EB-3332-851	EB-3332-852	EB-3332-851C1	EB-3332-851C2	EB-3332-851C3	
Processor	DM&P Vortex86DX2 (933MHz)					
BIOS	AMI BIOS					
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin					
Maximum Resolution	1920 x 1440 pixels					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Line out					
I/O	SD Slot	1x				
	SATA	1x				
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	N/A	RS-485	RS-232	RS-232	RS-232
	COM3		N/A	N/A	RS-232	RS-232
COM4	N/A		N/A	N/A	RS-232	
Auto Power On	Yes					
Power	DC +8V~+24V					
Dimensions	115 x 115 x 35mm					
Unit Net Weight	510g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. mPCIe (2.5" SATA HDD not support)					
Note	RS-232 COM ports in Full 9pin					

Model Type	EB-3330-852C1	EB-3330-852C2	EB-3330-851221	EB-3330-851221C1	EB-3330-851221C2	
	EB-3332-852C1	EB-3332-852C2	EB-3332-851221	EB-3332-851221C1	EB-3332-851221C2	
Processor	DM&P Vortex86DX2 (933MHz)					
BIOS	AMI BIOS					
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin					
Maximum Resolution	1920 x 1440 pixels					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Line out					
I/O	SD Slot	1x				
	SATA	1x				
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3	RS-232	RS-232	N/A	RS-232	RS-232
COM4	N/A	RS-232	N/A		RS-232	
Auto Power On	Yes					
Power	DC +8V~+24V					
Dimensions	115 x 115 x 35mm					
Unit Net Weight	510g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. mPCIe (2.5" SATA HDD not support)					
Note	RS-232 COM ports in Full 9pin					

### Features:

- DM&P Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- SATA DOM, 2.5" HDD, SSD support
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-485 Up to 2 ports (Optional)
- RS-232 Up to 3 ports (Optional)
- RS-422 port x 1 (Optional)
- Auto Power On support
- Ultra low power

