



EBOX-333x Series, LAN x 3, RS-232, SATA

Model Type	EB-3330-L3U4C1	
	EB-3332-L3U4C1	
Processor	DM&P Vortex86DX2 (933MHz)	
BIOS	AMI BIOS	
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series	
VGA	Integrated Graphics Chip/ D-Sub 15-pin	
Maximum Resolution	1920 x 1440 pixels	
Ethernet	LAN 2: 10/100 Mbps (RJ-45 connector, Built-in PXE diskless boot)	
	LAN 1 & LAN 3: 1G LAN (RJ-45 connector, use Realtek RTL8111F)	
USB 2.0	External: 4 ports (Front x 2, Rear x 2)	
HD Audio	Mic in and Line out	
I/O	SD Slot	1x
	SATA	1x (not support 2.5" SATA HDD)
	COM1	RS-232
Auto Power On	Yes	
Power	DC +8V~+24V	
Dimensions	115 x 115 x 35mm	
Unit Net Weight	510g	
Operation Temp.	5~50 °C	
Certifications	CE, FCC, VCCI	
Optional	TTL Level RS-232	
Note	RS-232 COM port in Full 9pin	

Features:

- * DM&P Vortex86DX2 (933MHz)
- * Onboard 1GB/ 2GB DDR2
- * SATA DOM support
- * VESA mounting support
- * Fanless design
- * PXE Diskless Boot
- * 1 Gbps LAN x 2
- * 10/100 Mbps LAN x 1
- * USB 2.0 port x 4
- * RS-232 port x 1
- * Auto Power On support
- * Ultra low power