

EBOX-336x Series, LAN x 1, RS-232, CANbus, SATA

| Model Type | EB-3360-SSB1 | EB-3360-B1C1G2 | EB-3360-B1C1 | EB-3360-B1C2 | EB-3360-B1C3 |
|--------------------|--|----------------|--------------|--------------|--------------|
| | EB-3362-SSB1 | EB-3362-B1C1G2 | EB-3362-B1C1 | EB-3362-B1C2 | EB-3362-B1C3 |
| Processor | DM&P Vortex86DX3 (1GHz) | | | | |
| BIOS | AMI BIOS | | | | |
| Memory | Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series | | | | |
| VGA | Integrated Graphics Chip/ D-Sub 15-pin | | | | |
| Maximum Resolution | 1920 x 1080 pixels | | | | |
| Ethernet | 10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot) | | | | |
| USB 2.0 | External: 3 ports (Front x 2, Rear x 1) Internal: 1 port | | | | |
| HD Audio | Line out | | | | |
| I/O | SD Slot | 1x | | | |
| | SATA | 1x | | | |
| | COM1 | N/A | 8-bit GPIO | N/A | RS-232 |
| | COM2 | | 8-bit GPIO | | RS-232 |
| | COM3 | | RS-232 | RS-232 | N/A |
| COM4 | CANbus | CANbus | CANbus | CANbus | |
| Auto Power On | Yes | | | | |
| Power | DC +8V~+24V | | | | |
| Dimensions | 115 x 115 x 35mm | | | | |
| Unit Net Weight | 510g | | | | |
| Operation Temp. | 5~50°C | | | | |
| Certifications | CE, FCC, VCCI | | | | |
| Optional | 1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. mPCIe (2.5" SATA HDD not support) | | | | |
| Note | RS-232 COM ports in Full 9pin | | | | |

Features:

- DM&P Vortex86DX3 (1GHz)
- Onboard 1GB/ 2GB DDR3
- SATA DOM, 2.5" HDD, SSD support
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-232 Up to 3 ports (Optional)
- CANbus port x 1
- 8-bit GPIO port x 2
- Auto Power On support
- Ultra low power

