

EBOX-336x Series, LAN x 1, RS-485, mPCIe

Model Type	EB-3360-851P	EB-3360-852P	EB-3360-851C1P	EB-3360-851C2P	EB-3360-851C3P	
	EB-3362-851P	EB-3362-852P	EB-3362-851C1P	EB-3362-851C2P	EB-3362-851C3P	
Processor	DM&P Vortex86DX3 (1GHz)					
BIOS	AMI BIOS					
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin					
Maximum Resolution	1920 x 1080 pixels					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Line out					
I/O	SD Slot	1x				
	mPCIe	1x				
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	N/A	RS-485	RS-232	RS-232	RS-232
	COM3		N/A	N/A	RS-232	RS-232
COM4	N/A		N/A	N/A	RS-232	
Auto Power On	Yes					
Power	DC +8V~+24V					
Dimensions	115 x 115 x 35mm					
Unit Net Weight	510g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot 5. SATA (not support 2.5" SATA HDD)					
Note	RS-232 COM ports in Full 9pin					

Model Type	EB-3360-852C1P	EB-3360-852C2P	EB-3360-851221P	EB-3360-851221C1P	EB-3360-851221C2P	
	EB-3362-852C1P	EB-3362-852C2P	EB-3362-851221P	EB-3362-851221C1P	EB-3362-851221C2P	
Processor	DM&P Vortex86DX3 (1GHz)					
BIOS	AMI BIOS					
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin					
Maximum Resolution	1920 x 1080 pixels					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Line out					
I/O	SD Slot	1x				
	mPCIe	1x				
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3	RS-232	RS-232	N/A	RS-232	RS-232
COM4	N/A	RS-232	N/A		RS-232	
Auto Power On	Yes					
Power	DC +8V~+24V					
Dimensions	115 x 115 x 35mm					
Unit Net Weight	510g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot 5. SATA (not support 2.5" SATA HDD)					
Note	RS-232 COM ports in Full 9pin					

Features:

- DM&P Vortex86DX3 (1GHz)
- Onboard 1GB/ 2GB DDR3
- SATA DOM, 2.5" HDD, SSD support
- mPCIe DOM, SSD support
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-485 Up to 2 ports (Optional)
- RS-232 Up to 3 ports (Optional)
- RS-422 port x 1 (Optional)
- Auto Power On support
- Ultra low power

