

## EBOX-336x Series, LAN x 2, 8-bit GPIO, SATA, mPCIe

### Features:

- DM&P Vortex86DX3 (1GHz)
- Onboard 1GB/ 2GB DDR3
- SATA DOM, 2.5" HDD, SSD support
- mSATA support (mSATA to SATA adapter required)
- mPCIe DOM, SSD support (Optional)
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- 8-bit GPIO port x 2
- RS-232 Up to 2 ports (Optional)
- Auto Power On support
- Ultra low power



Model Type	EB-3360-L2SSG2	EB-3360-L2C1G2	EB-3360-L2C2G2	EB-3360-L2SSG2P	EB-3360-L2C1G2P	EB-3360-L2C2G2P	
	EB-3362-L2SSG2	EB-3362-L2C1G2	EB-3362-L2C2G2	EB-3362-L2SSG2P	EB-3362-L2C1G2P	EB-3362-L2C2G2P	
Processor	DM&P Vortex86DX3 (1GHz)						
BIOS	AMI BIOS						
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series						
VGA	Integrated Graphics Chip/ D-Sub 15-pin						
Maximum Resolution	1920 x 1080 pixels						
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)						
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port						
HD Audio	Line out						
I/O	SD Slot	1x					
	SATA	1x			N/A		
	mPCIe	N/A			1x		
	COM1	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO
	COM2	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO	8-bit GPIO
	COM3	N/A	RS-232	RS-232	N/A	RS-232	RS-232
COM4	N/A		RS-232	N/A		RS-232	
Auto Power On	Yes						
Power	DC +8V~+24V						
Dimensions	115 x 115 x 35mm						
Unit Net Weight	510g						
Operation Temp.	5~50°C						
Certifications	CE, FCC, VCCI						
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot						
	mPCIe (2.5" SATA HDD not support)			SATA (not support 2.5" SATA HDD)			
Note	RS-232 COM ports in Full 9pin						