



Model Types	EB-3360-C2DMI/ EB-3360-L2C2DMI		EB-3360-852DMI/ EB-3360-L2852DMI	
	EB-3362-C2DMI/ EB-3362-L2C2DMI		EB-3362-852DMI/ EB-3362-L2852DMI	
Processor	DM&P Vortex86DX3 Dual core 1GHz			
BIOS	AMI BIOS			
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series			
HDMI	HDMI V1.4 (max. 1920×1080@60Hz)			
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port			
HD Audio	Mic in and Line out			
Extension I/F	Standard Mini PCIe x 1 for WiFi/ BT Module (when USB signal device in use, Internal USB port not available)			
I/O	SD Slot	1x (SD, SDHC support)		
	SATA	1x		
	COM1	RS-232	RS-485	
	COM2	RS-232	RS-485	
Auto Power On	Yes			
Fanless	Yes			
Power	DC +8V~+24V			
Dimensions	115 x 115 x 35mm/ 100x100mm VESA support			
Unit Net Weight	510g			
Operation Temp.	0~60 °C/ -20~60 °C			
Certifications	CE, FCC, VCCI			
Optional	1. Internal SD Card slot 2. TTL Level RS-232			
Note	SATA 2.5" HDD not available due to space limited			