

## EBOX-333x Series, LAN x 2, RS-422, mPCIe

### Features:

- DM&P Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- mPCIe DOM, SSD support
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-422 Up to 2 ports (Optional)
- RS-232 Up to 3 ports (Optional)
- Auto Power On support
- Ultra low power



27

Model Type	EB-3330-L2221P	EB-3330-L2222P	EB-3330-L2221C1P	EB-3330-L2221C2P	EBO3330-L2221C3P	EB-3330-L2222C1P	EB-3330-L2222C2P	
	EB-3332-L2221P	EB-3332-L2222P	EB-3332-L2221C1P	EB-3332-L2221C2P	EBO3332-L2221C3P	EB-3332-L2222C1P	EB-3332-L2222C2P	
Processor	DM&P Vortex86DX2 (933MHz)							
BIOS	AMI BIOS							
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series							
VGA	Integrated Graphics Chip/ D-Sub 15-pin							
Maximum Resolution	1920 x 1440 pixels							
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)							
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port							
HD Audio	Line out							
I/O	SD Slot	1x						
	mPCIe	1x						
	COM1	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422
	COM2	N/A	RS-422	RS-232	RS-232	RS-232	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232
COM4	N/A		N/A	N/A	RS-232	RS-232	N/A	RS-232
Auto Power On	Yes							
Power	DC +8V~+24V							
Dimensions	115 x 115 x 35mm							
Unit Net Weight	510g							
Operation Temp.	5~50°C							
Certifications	CE, FCC, VCCI							
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. SIM Card slot 5. SATA (not support 2.5" SATA HDD)							
Note	RS-232 COM ports in Full 9pin							